



**ZINC OXIDE  
GRADE AZO66L**

**Description & Uses**

Grade AZO66L is a large particle, extremely pure French Process, statistically controlled zinc oxide produced from zinc metal. AZO66L is used by the zinc chemical, paint, and coating industries and in those applications which derive benefits from larger than normal high purity particles. Grade AZO66L is available with the surface treatment (AZO66LT) and in a pelleted form (AZO66LP).

**Typical Technical Values\***

<b>Chemical Analysis (%)</b>	<b>Range</b>	<b>Nominal</b>	<b>Method</b>
ZnO (Zinc Oxide)	≥ 99.7%	99.8%	USP
Pb (Lead)	≤ 0.005%	0.003%	USP
Cd (Cadmium)	≤ 0.003%	0.001%	USP
Cu (Copper)	≤ 0.002%	nil	USP
Fe (Iron)	≤ 0.002%	nil	USP

**Physical Properties**

Surface Area (m <sup>2</sup> /g)	3.0-5.0	4.0	D4315
Fineness passing 325 mesh (%)	≥99.9	99.98	D4315
Heat Loss/Moisture (%)	< 0.2%	0.1%	D280
Specific Gravity	N/A	5.6	USZ
Apparent Density (Powder)	20-40	30	USZ
Apparent Density (Pellets)	50-85	70	USZ

Standard packaging in 50 pound net weight bags on 48X40 wood pallets. 2,500 pounds net weight.

*\*U.S. Zinc can produce Zinc Oxide to meet individual customer specifications superseding the above. Please contact customer service for additional information.*

Revised 02/18/2015

**U. S. ZINC**

2727 Allen Parkway, Suite 800 Houston TX 77019 USA.

Phone (001) 713-926-1705, Fax (001) 713-924-4828

[Info@USZinc.com](mailto:Info@USZinc.com) [WWW.USZinc.com](http://WWW.USZinc.com)