# SAFETY DATA SHEET



Date of issue/Date of revision 22 November 2016

**Version 4** 

# **Section 1. Identification**

Product name : Hi-Sil™ EZ160G

Product code : 8010462

Other means of identification

: Synthetic Precipitated Silicas; Hydrated Amorphous Silica; Silicon Dioxide; SiO2

Product type : Solid.

#### Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.

Use of the substance/

mixture

: Industrial applications including, but not limited to Paints, Coatings, Food/feedstuff

additives, Manufacture of footwear, Carriers, or Reinforcing agent in rubber.

Uses advised against : None identified.

Manufacturer : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272

PPG Industries Chemicals BV PO Box 181, 9930 - AD, Delfzijl, The Netherlands

**Emergency telephone** 

number

: (412) 434-4515 (U.S.)

Technical Phone Number : 1-800-243-6745 (Silica) 8am-5pm Eastern time

### Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

**GHS label elements** 

Signal word : No signal word.

**Hazard statements**: No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

United States Page: 1/11

Product code 8010462 Date of issue 22 November 2016 Version 4

Product name Hi-Sil™ EZ160G

### Section 2. Hazards identification

Disposal : Not applicable.

Supplemental label elements

: No known significant effects or critical hazards.

**Hazards not otherwise** 

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Substance

Product name : Hi-Sil™ EZ160G

Other means of identification

: Synthetic Precipitated Silicas; Hydrated Amorphous Silica; Silicon Dioxide; SiO2

#### **CAS** number/other identifiers

**CAS number** : 1/12926-00-8

Ingredient name	%	CAS number
Silica, amorphous, precipitated and gel	>87	112926-00-8

Contains no detectable crystalline silica (detection limit <0.1% by weight).

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep

person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No significant irritation expected other than possible mechanical irritation.

Inhalation :

United States Page: 2/11

Date of issue 22 November 2016 Version 4

Product code 8010462

Product name Hi-Sil™ EZ160G

### Section 4. First aid measures

Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contact : Prolonged or repeated contact may dry skin and cause irritation.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> irritation redness

Inhalation : Adverse symptoms may include the following:

coughing

Respiratory tract irritation

**Skin contact** : Adverse symptoms may include the following:

dryness

Ingestion No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

**Specific treatments** No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : No specific fire or explosion hazard. When transferring material into flammable solvents, use proper grounding to avoid electrical sparks.

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Special protective actions for fire-fighters

**Special protective** equipment for fire-fighters : No action shall be taken involving any personal risk or without suitable training.

: No special protection is required.

**United States** Page: 3/11 Product code 8010462

Product name Hi-Sil™ EZ160G

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Product forms slippery surface when combined with water.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Vacuum or sweep up material and place in a designated, labeled waste container.

Large spill

: Vacuum or sweep up material and place in a designated, labeled waste container.

Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

### Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** Advice on general occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. When transferring material into flammable solvents, use proper grounding to avoid electrical sparks. Avoid alteration of product properties before use. Calcining (which may result in crystalline formation) or mixing with additives may alter toxicological properties.

See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Do not store in unlabeled containers.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits
Silica, amorphous, precipitated and gel	None.

#### Key to abbreviations

= Acceptable Maximum Peak

S = Potential skin absorption

**United States** Page: 4/11

= Respiratory sensitization

= Short term Exposure limit values

= Skin sensitization

Product code 8010462

Product name Hi-SiI™ EZ160G

# Section 8. Exposure controls/personal protection

= American Conference of Governmental Industrial Hygienists. ACGIH

С = Ceiling Limit F = Fume

IPEL = Internal Permissible Exposure Limit

**OSHA** 

Ζ = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

TD = Total dust = Occupational Safety and Health Administration. TLV = Threshold Limit Value R = Respirable TWA = Time Weighted Average

#### Consult local authorities for acceptable exposure limits.

# procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

SS

STEL

#### Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

#### **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection Skin protection

: Safety glasses with side shields.

## **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### **Gloves**

Prolonged or repeated contact may dry skin and cause irritation. For prolonged or repeated handling, gloves of any kind are recommended. For example: Leather, Cloth, or Rubber gloves.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

> **United States** Page: 5/11

Product code 8010462

Product name Hi-Sil™ EZ160G

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Powder., Solid. or Granular solid..

Color : White. Odor : Odorless. **Odor threshold** : Not available.

pН : 5.2 to 7.5 [5% Suspension]

**Melting point** : Not applicable. **Boiling point** : Not applicable

Flash point : Closed cup: Not applicable.

: Not available. **Auto-ignition temperature Decomposition temperature**: Not available. Flammability (solid, gas) : Not applicable Lower and upper explosive : Not available.

(flammable) limits

**Evaporation rate** : Not applicable Vapor pressure : Not applicable. Vapor density : Not applicable. **Relative density** : 2.1 (silicon dioxide)

Density (lbs/gal) 17.53 **Solubility** : Insoluble Partition coefficient: n-

octanol/water

: Not available.

**Viscosity** : Not applicable. **Volatility** : 0% (w/w) % Solid. (w/w) : 100

## Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : High temperature (>800 C) treatment (calcining). Avoid alteration of product properties

before use. Calcining (which may result in crystalline formation) or mixing with additives

may alter toxicological properties.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** Reactive or incompatible with the following materials: acids, oxidizing materials, strong

alkalis.

**United States** Page: 6/11 Date of issue 22 November 2016 Version 4

Product name Hi-Sil™ EZ160G

## Section 10. Stability and reactivity

Hazardous decomposition

Product code 8010462

: Under normal conditions of storage and use, hazardous decomposition products should

**products** not be produced.

# **Section 11. Toxicological information**

#### Information on toxicological effects

**Acute toxicity** 

**Conclusion/Summary**: No known significant effects or critical hazards.

Irritation/Corrosion
Conclusion/Summary

Skin
 Eyes
 No known significant effects or critical hazards.
 Respiratory
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

**Sensitization** 

**Conclusion/Summary** 

Skin: No known significant effects or critical hazards.Respiratory: No known significant effects or critical hazards.

**Mutagenicity** 

**Conclusion/Summary**: No known significant effects or critical hazards.

**Carcinogenicity** 

**Conclusion/Summary**: No known significant effects or critical hazards.

Classification

Product/ingredient name	OSHA	IARC	NTP
Silica, amorphous, precipitated and gel	-	3	-

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA:

Not listed/not regulated: -

Reproductive toxicity

**Conclusion/Summary**: No known significant effects or critical hazards.

**Teratogenicity** 

**Conclusion/Summary**: No known significant effects or critical hazards.

**Specific target organ toxicity (single exposure)** 

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which may cause damage to the following organs: upper respiratory

tract, eyes.

#### **Aspiration hazard**

United State	es Page: 7/11
--------------	---------------

Product code 8010462

Product name Hi-Sil™ EZ160G

# Section 11. Toxicological information

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

**Eye contact**: No significant irritation expected other than possible mechanical irritation.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

**Skin contact**: Prolonged or repeated contact may dry skin and cause irritation.

**Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

irritation redness

**Inhalation**: Adverse symptoms may include the following:

coughing

Respiratory tract irritation

**Skin contact**: Adverse symptoms may include the following:

dryness

**Ingestion** : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed an average time span of 8.6 years. Of these 165 workers, 44 had been exposed for an average of 18 years. No adverse effects were noted in complete medical examinations (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposures. Laboratory studies have also been conducted in small animals via inhalation of levels of precipitated silica dust of up to 126 mg/cu.m. per periods from six months to two years. Although precipitated silica was temporarily deposited in the animals' lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, PPG indicate a very low order of pulmonary activity for synthetic precipitated silicas. PPG recommends that persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Short term exposure

Potential immediate : No significant irritation expected other than possible mechanical irritation.

effects

Potential delayed effects : Prolonged or repeated contact may dry skin and cause irritation.

Long term exposure

<u>ong term exposure</u>

Potential immediate effects

Potential delayed effects : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

No known significant effects or critical hazards.

United States Page: 8/11

Product code 8010462 Date of issue 22 November 2016 Version 4

Product name Hi-SiI™ EZ160G

# **Section 11. Toxicological information**

**Fertility effects** 

: No known significant effects or critical hazards.

Not available.

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Silica, amorphous, precipitated and gel	NOEC >1000 ppm	Daphnia - Daphnia magna	24 hours
prodipitation and go.	Acute NOEC >10000 ppm Fresh water	Fish	96 hours Static
	Acute NOEC >10000 ppm	Fish - Brachydanio rerio	4 days Static

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Silica, amorphous, precipitated and gel	-	-	Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Silica, amorphous, precipitated and gel	-	0	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

United States Page: 9/11

Date of issue 22 November 2016 Version 4

Product code 8010462

Product name Hi-Sil™ EZ160G

### 14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	None.	-	-
Packing group	-	-	-
<b>Environmental hazards</b>	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

DOT : None identified.IMDG : None identified.IATA : None identified.

Special precautions for user : -

# Section 15. Regulatory information

#### **United States**

United States inventory (TSCA 8b): All components are listed or exempted.

U.S. Federal regulations

**SARA 302/304** 

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

**SARA 311/312** 

Classification : Not applicable.

Composition/information on ingredients

No products were found.

## **Section 16. Other information**

Hazardous Material Information System (U.S.A.)

Health: 1 Flammability: 0 Physical hazards: 0

( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

United States Page: 10/11

Product code 8010462 Date of issue 22 November 2016 Version 4

Product name Hi-Sil™ EZ160G

### Section 16. Other information

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 1 Flammability: 0 Instability: 0

Other information : the PPG logo is a registered trademark of PPG Industries Ohio, Inc.

Date of previous issue : 1/27/2016

Organization that prepared

the MSDS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

: EHS

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

#### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 11/11