

CARBOMIX® Black Masterbatch

1605, 1620

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical name	Styrene-Butadiene Rubber, Carbon Black Masterbatch
Supplier	Lion Copolymer LLC
	5955 Scenic Highway, Baton Rouge, LA 70805
Emergency telephone	(225) 267-3608
E-mail:	SBR.MSDS@lioncopolymer.com
Product use	General purpose rubber articles and rubber modified articles

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	<u>CAS #</u>	<u>EINECS #</u>	<u>Max.Wt.%</u>	<u>Hazard Classification</u>
Styrene-Butadiene copolymer	9003-55-8	NA (polymer)	67	NH
Carbon Black	1333-86-4	215-609-9	33	Possible Carcinogen
Disproportionated Tall Oil	61790-12-3	263-107-3	6	Irritant
Disproportionated Rosin	8050-09-7	232-475-7	6	Sensitizer (Xn, R43)

3. HAZARDS IDENTIFICATION

Human health hazards:	Heating ma	ay release small a	mounts of volatile irrita	ints.
Environmental hazards:	Not availab	ole.		
Physical/chemical hazards:	The materi	ial burns slowly wit	h high smoke density.	
HMIS Hazard Classification:	Health: 1	Flammability: 1	Physical Hazard: 0	Protection: B

4. FIRST AID MEASURES

Inhalation:	If fumes/vapors are inhaled, move to fresh air, aid breathing if necessary. Get medical attention if irritation persists.	
Eye Contact:	Remove as for any foreign object. Flush with clean water for 15 minutes. Get medical attention if irritation persists.	
Skin Contact: Ingestion:	Wash with soap and water. Get medical attention if irritation develops or persists. Unlikely to occur. Contact Poison Control Center.	
Note to physician:	Treat symptomatically.	

5. FIRE FIGHTING MEASURES

Water, water/foam, carbon dioxide, ABC fire extinguisher powder.
a:No restrictions.
None known.
Carbon monoxide, carbon dioxide, incomplete combustion products.
Fire fighters should wear full protective clothing including self-contained breathing
apparatus. Keep personnel removed and upwind of fire.
Health: 1 Flammability: 1 Reactivity: 0 Special:

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Use protective gloves (see section 8).
Methods for cleanup:	In case of large spills: Collect spilled material and reuse if possible. In case of small
	spills: collect spilled material in containers, and dispose appropriately.



CARBOMIX® Black Masterbatch

1605, 1620

7.	HANDLING AND STORAG	E	
	Handling	When using do not eat, drink or smoke. Avoid inhalation of fumes/vapors from hot rubbers, compounds and vulcanizates. Avoid repeated or prolonged contact with skin. Wear gloves and wash hands after handling.	
	Storage	Store in a clean, dry, dark area to maintain product quality. Keep in original containers or use black covers to protect from artificial or natural light. Outdoor storage should be avoided; the preferred storage temperature is 15-25 C. NFPA Class IIIB Storage, Flash point > 200F.	
8.	EXPOSURE CONTROLS/PERSONAL PROTECTION		
	Exposure Limit Values Engineering controls	Not defined for this material A ventilation system should be installed where processing at high temperatures e.g. vulcanization, is carried out and where bales are being ground or machined. Local exhaust ventilation is recommended during all hot processing operations.	
	Personal protection	5 1 5 1	
	General	General hygiene considerations are appropriate when used as recommended. The following precautions are recognized as common good industrial hygiene practice. Emergency conditions may require additional precautions.	
	Respiratory	Not normally required at ambient temperatures. Avoid inhalation of fumes/vapors from hot rubbers, compounds and vulcanizates. If processing in area where ventilation is inadequate or ignition has occurred, wear a NIOSH-approved organic vapor respirator.	
	Eyes & Skin	Wear heat resistant gloves, arm protection and face shield when working with hot material. Avoid contact with eyes and skin and wash thoroughly after handling and before eating or drinking.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor pH: Boiling point/ Range Flash Point Flammability: Explosive properties: Oxidizing properties: Vapor pressure: Relative density: Solubility in water: Solubility in fats/ oils Partition Coefficient (n-octanol-water):	Solid, Bales Black with gray bale coating Odorless to weak aromatic NA Not established > 300 C No, but the product will burn if ignited. Not explosive Not an oxidizer NE, Negligible 1.10 – 1.15 Insoluble NE
Viscosity	NE
Vapor Density	NA
Evaporation rate:	NA
Volatile (% by weight, @105°0	C):0.75 max
Auto Ignition Temperature:	> 246 C (475 F)
Decomposition temperature	> 300 C



CARBOMIX® Black Masterbatch

1605, 1620

10. STABILITY AND REACTIVITY

Chemical Stability:	Product is stable at ambient temperature and pressure.	
Conditions to Avoid:	Extreme temperature, 300-350 C (572-662 F) will cause thermal decomposition.	
Incompatible Materials:	Strong oxidizers.	
Hazardous Decomp. Products:Carbon monoxide, silicates and partially oxidized hydrocarbons.		
Hazardous Reactions:	Will not occur.	

11. TOXICOLOGICAL INFORMATION

Toxicity to Humans	Components are skin sensitizers or may be irritants.
Toxicity to Animals	Components are skin sensitizers or may be irritants.
Components:	May cause sensitization by inhalation and skin contact. See Section 15.

12. ECOLOGICAL INFORMATION

Not available
Not available
Not available
Not available.

13. DISPOSAL CONSIDERATIONS

Methods of disposal Reuse if possible. Material as supplied is not characterized as hazardous under RCRA (Resource and Conservation Recovery Act). Dispose of contaminated materials and other waste materials as directed by local, state and federal regulations. Improper disposal of excess wastes is a violation of federal law.

14. TRANSPORT INFORMATION

USA	Not regulated as hazardous by DOT regulations.
Canada	Not regulated as hazardous by Canadian Transportation of Dangerous Goods
	Regulations
Europe	Not regulated as hazardous by European Transportation of Dangerous Goods
	Regulations
Canada	Not regulated under the Canadian Transportation of Dangerous Goods Regulations.
IATA	Not regulated.

15. REGULATORY INFORMATION

OSHA FDA:	Tall oil and Rosin acids are irritants. The following products may be used in compliance with 21 CFR 177.2600, 'Rubber
	Articles Intended for Repeated Use': 1605, 1620
SARA Title III:	Section 302/304. Extremely Hazardous Substances - None. Section 311/312. None.
	Section 313. None
TSCA & EINECS	Components are listed
CA65	Unbound, respirable Carbon black is "Known to California to Cause Cancer or Reproductive Effects".
EU Phrases:	Symbol: Xn Harmful Risk Phrases: R43, May cause sensitization by skin contact Safety Phrases: S2-24-37 Contains: Disproportionated rosin acid.



CARBOMIX® Black Masterbatch 1605, 1620

16. OTHER INFORMATION

None of the materials referenced herein should be used and/or applied in any product, device or material used or for use as human body implant or otherwise within the human body.

Recommended application(s): Elastomeric component in rubber compounds, for applications in automotive, construction, wire and cable and general rubber goods

EU Safety Phrases: S2, Keep out of the reach of children; S24, Avoid contact with skin; S37, Wear suitable gloves.

All information supplied by or on behalf of Lion Copolymer in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Lion Copolymer assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Lion Copolymer for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.

Revision History:Date Prepared:6/28/2011 by Larry HarrisSupersedes:2/2/2006MSDS ID:SBR 1605