

Material Safety Data Sheet FLXP0012

Date of Printing: 12/08/2000

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: SANTOCURE CBS

MSDS NO. FLXP0012

Chemical Name: N-Cyclohexyl-2-benzothiazolesulfenamide

Synonyms: Perkacit CBS; Santocure, CBS; 2-Benzothiazolesulfenamide, N-cyclohexyl-

Use: Accelerator.

Manufactured By: Flexsys America L.P. 260 Springside Drive Akron OH 44333 USA
Emergency Telephone: CHEMTREC: 1-800-424-9300 (TOLL FREE - USA and Territories)

703-527-3887 (ELSEWHERE - Collect Calls Accepted)

CANUTEC: 613-996-6666 (Canada) **SETIQ:** 91-800-00-214 (Mexico)

Prepared By: Flexsys America Product Safety Phone (330) 668-8281 FAX (330) 668-8281

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components/CAS#	Percent
N-Cyclohexyl-2-	96-99
benzothiazolesulfenamide	
95-33-0	
Additive Package	0.5-2.5
Various	
2-Mercaptobenzothiazole	0-1
149-30-4	
Cyclohexylamine	
108-91-8	
Mercaptobenzothiazole	0-1
Disulfide	
120-78-5	
Benzothiazole	
95-16-9	

3. HAZARDS IDENTIFICATION

Hazard Information

Emergency Overview: WARNING! Combustible dust - explosion potential. Keep away from heat, sparks, and flame. This

material is irritating to skin, eyes and respiratory tract.

Eye Contact: Causes eye irritation. Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain,

tearing, and hazy vision.



Responsible Care

Page 1 of 6

MARKETED BY
HARWICK STANDARD
DISTRIBUTION CORPORATION
60 S. Selberling Street • Akron, Ohio 44305

Skin Contact: May cause an allergic skin reaction. May cause a rash and itching of the skin. May cause skin

defatting with prolonged exposure.

Inhalation: Causes moderate respiratory irritation. Irritating vapor causes immediate distress. Irritates mucous

membranes. Irritation (upper respiratory): signs/symptoms can include soreness of the nose and

throat, coughing and sneezing.

Ingestion: May be harmful if large amounts are swallowed. May cause liver and kidney damage.

4. FIRST AID MEASURES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get

medical attention if irritation persists.

On Skin: Remove containinated clothing, wash skin with water, using soap if available. Remove

contaminated clothing and launder before reuse. Get medical attention if irritation persists.

Inhaled: Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get

immediate medical attention.

Swallowed: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician.

Never give anything by mouth to an unconscious person.

Notes To Physician: Provide symptomatic/supportive care as necessary. Treatment based on sound judgment of

physician and individual reactions of patient. Observe for signs of respiratory distress.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): 350°F / 177°C
Flash Point Method: Cleveland Open Cup
Autoignition Temp. (°F/C): 660°F / 349°C (Dust)
Lower Explosion Limit in Air (LEL): Not Determined
Upper Explosion Limit in Air (UEL): Not Determined.

Extinguishing Media: Water fog, carbon dioxide, foam, dry chemical

Special Exposure Hazards: Fight fire from a safe distance and from a protected location. Flammable dust when

in finely divided and highly suspended state. Use water spray to cool fire exposed surfaces. Decomposition in fire may produce toxic gases. Do not allow runoff to

enter waterways.

Special Protective Equipment: Fire fighters should wear full protective clothing, including self-contained breathing

equipment:

Unusual Fire/Explosion Hazards: Toxic emissions may result if product is involved in a fire. Fire produces highly

toxic sulfur dioxide gas

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wear protective equipment specified. Avoid the generation of dust. Sweep,

vacuum, or shovel and place into closable container for disposal.

Procedure for Cleaning/Absorption: Isolate area and remove sources of friction, impact, heat, low level electrical

current, and RF energy. Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Scoop up and remove. Do NOT spread

spilled product with water.

CERCLA Reportable Quantity (RQ): Not Applicable

7. HANDLING AND STORAGE

Handling: Good hygienic practices should be observed. Work clothes should be washed seperately at the end of each

work day. Disposable clothing should be discarded with material. Avoid generating or breathing dust. Avoid contact with eyes, skin and clothing. Reclose containers of unused product. Wash hands before eating,



drinking, chewing gum, using tobacco or using the toilet. Do not reuse this container.

Storage: Store closed containers in a cool, dry, well-ventilated area. Store away from strong oxidizing materials.

Avoid exposure to direct sunlight. Do not store near Crystex Insoluble Sulfur. Slowly degrades and releases

irritating vapors under warm, humid conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles to protect against exposure. Eye protection is not required

during typical product use conditions

Skin Protection: Normal work coveralls. Launder contaminated clothing before reuse.

Gloves: Use gloves as a standard industrial handling procedure. All cleanable impervious glove

types are acceptable.

Respiratory Protection: Appropriate respiratory protection shall be worn when applied engineering controls are not

adequate to protect against inhalation exposure. Firefighting; use a Positive Pressure

Demand Full Face Self Contained Breathing Apparatus.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within

their exposure limits during the use of this product. Adequate ventilation should be provided

to keep dust concentrations below acceptable exposure limits. Discharge from the ventilation system should comply with the applicable air pollutions control regulations.

Eliminate ignition sources.

Airborne Exposure Limits: Nuisance Dust. OSHA PEL/8Hr-TWA = 15 mg/m3 (Total Dust). OSHA PEL/8-Hr TWA = 05

mg/m3 (Respirable Dust). ACGIH TLV/8-Hr TWA = 10 mg/m3. Cyclohexylamine: ACGIH

TLV/8Hr TWA = 10 ppm. NIOSH REL/8Hr TWA = 10 ppm.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Off-white powder White to off-white granules.

Odor: MILD AMINE

pH: N/A

Specific Gravity: 1.3 @ 25°C

Density: Unknown

Bulk Density: 1280 kg/m3

Melting Point (°F/C): 97-105°C

Boiling Point (°F/C): Not Determined

Vapor Pressure: Negligible

Vapor Density (Air=1): Not Determined

% Volatile by Volume: <0.5% Solubility in Water: INSOLUBLE

Other Solubility: Soluble in Acetone Ether Ethanol

Viscosity: Not determined.

Other Data: Ash content = 0.3% max.

Molecular Weight: 264.4

Molecular Formula: C13-H16-S2-N2

10. STABILITY AND REACTIVITY

Chemical Stability: Stable when stored at room temperature in closed, original container. Stable under

normal conditions of handling, use and transportation. Stable if protected from heat

and exposure to air. Loses potency with time Protect from moisture

Hazardous Polymerization: Will not occur

Conditions to Avoid: Keep away from heat, sparks and flame.

Materials to Avoid: Reducing agents. Contact with acids. Avoid contamination of product with small

amounts of water. Do not store near Crystex Insoluble Sulfur.

Hazardous Decomposition Products: Carbon monoxide Oxides of nitrogen Oxides of sulfur Amines

Additional Guidelines: Amine vapors can cause insoluble sulfur to revert to soluble form.

Responsible Care
Page 3 of 6

11. TOXICOLOGICAL INFORMATION

Target Organs

Acute Oral LD50 (mg/kg): 5300 mg/kg
Acute Dermal LD50 (mg/kg): >7940 mg/kg
Acute Inhalation LC50 (mg/l): Not Determined

Principle Routes of Exposure: Eyes. Inhalation. Dermal - skin.

Ingestion: May be harmful if large amounts are swallowed. May cause liver and kidney

damage.

Skin Contact: May cause an allergic skin reaction. May cause a rash and itching of the skin.

May cause skin defatting with prolonged exposure.

Inhalation: Causes moderate respiratory irritation. Irritating vapor causes immediate distress.

Irritates mucous membranes. Irritation (upper respiratory): signs/symptoms can

include soreness of the nose and throat, coughing and sneezing.

Eye Contact: Causes eye irritation. Moderate Eye Irritation: signs/symptoms can include

redness, swelling, pain, tearing, and hazy vision.

Aggravated Conditions: Pulmonary disorders. Dermal ailments. Eye, skin, respiratory, blood, liver and/or

kidney ailments. This material or its emissions may cause an allergic or

sensitization reaction and thereby aggravate systemic disease.

Carcinogenicity Comment: This product or one of its ingredients present 0.1% or more is NOT listed as a

carcinogen or suspected carcinogen by NTP, IARC, or OSHA. Carcinogenic:

Category 3

Other: Decomposition products and fumes from vulcanization and cross-linking may

cause eye, skin and respiratory sensitization. May be a skin sensitizer. Product

releases amine vapors during cure.

Primary Irritation Effect: Moderately irritating.

Carcinogenicity: Negative in standard tests using bacteria and yeast cells

Genotoxicity: None

Reproductive/Developmental

Toxicity:

No evidence of teratogenicity in animal studies using rats, mice and hamsters

12. ECOLOGICAL INFORMATION

Acute Fish Toxicity: 96Hr LC50 Rainbow Trout = 5.4 mg/l. 96Hr LC50 Bluegill Sunfish = 7.9 mg/l. 96Hr

LC50 Fathead Minnow = >1000 mg/l.

Acute Crustaceans Toxicity: 48Hr LC50 Daphnia Magna = 18.0 mg/l

Acute Algae Toxicity: 96Hr EC50 Algae (chlorophyll) = 1.1 ppm. 96Hr EC50 Algae (cell count) = 0.9 ppm.

Octanol/Water Coefficient: 4.93 log P

Chemical Fate Information: Biodegradability: 4% CO2 evolution

Other Information: Not Available

13. DISPOSAL CONSIDERATIONS

Disposal of Waste Method:

This material is not a RCRA hazardous waste. Bury in a licensed landfill or burn in an approved incinerator according to federal, state, and local regulations. Empty containers should be handled in a manner not to cause dusting during collection, transporation and disposal.

Contaminated Packaging:

If empty container retains product residues, all label precautions must be observed. Store away from ignition sources. Transport with all closures in place. Return for reuse or dispose according to national or local regulations. Dispose of container according to national or local regulations.



TRANSPORT INFORMATION

DOT:DOT Status: Not Regulated **DOT Shipping Name:** NONE None

DOT Reportable Quantity (lbs):

NOT REGULATED FOR TRANSPORTATION

ICAO/IATA:Status: **Proper Shipping Name:**

None NONE

UN/NA Number: IMDG:Status:

Not Regulated

Proper Shipping Name:

None

TDG (Canada):Status:

Not Regulated

Proper Shipping Name:

None

15. REGULATORY INFORMATION

Worldwide Inventory Status

TSCA (USA): Listed Canadian DSL: Listed Canadian NDSL: N/A Listed **EINECS/ELINCS (Europe):** Japanese Inventory (ENCS): Listed Korean Chemical Inventory (ECL): Listed Listed **Australian Chemical Inventories**

(AICS):

Listed New Zealand (NZ): Listed Phillipines (PICCS) Inventory: Listed China (CLECS):

US Regulatory Rules

None Found **SARA Section 302:**

SARA 311/312 Hazard Catagories: Immediate Delayed Fire 2-Mercaptobenzothiazole. SARA 313 Chemical: Not a RCRA waste. **RCRA Status:**

Other Regulations:

California Proposition 65: NONE **New Jersey Right-to-Know List:** N/A Pennsylvania Right to Know List: N/A Florida Right to Know: N/A Minnesota Right to Know: N/A N/A MA Right to Know Law:

Regulated for Use under the following sections of 21 CFR: 177.2600 Rubber FDA Status 21 CFR:

Articles Intended for Repeated Use in Food Contact.

Canadian Regulations

D2B TOXIC MATERIALS / Materials Causing Other Toxic Effects WHMIS Hazard Class:

N/A NPRI:

OTHER INFORMATION

Hazard Rating Systems:

HEALTH 2, FLAMMABILITY 1, REACTIVITY 0 **HMIS Classification:**



NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0

The following has been revised since the last issue of this MSDS:

Nothing has been revised.

Additional Information: The Additive package for this product may contain some of the following at levels up to 1%:

Butyl Oleate CAS# 142-77-8. White Mineral Oil CAS# 8042-47-5. Methylcellulose CAS#

9004-67-5.

Important Note: This information is furnished without warranty, expressed or implied, as to accuracy or

completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final

determination of suitability of any material is the sole responsibility of the user.

END OF MSDS

