



Chemicals Americas, Inc.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: **FLUON TL-102**
Product Code: 610102200
Trade Name: FLUON
Chemical Characterization: Powdered or granular PTFE mixture

Supplier:
AGC Chemicals Americas, Inc.
229 East 22nd Street
Bayonne, NJ 07002

24 Hr. Emergency Telephone Numbers
CHEMTREC (US) (800) 424-9300 24 hours
MEDICAL EMERGENCY: (800) 420-8479
Transportation Phone (800) 424-9300
Customer Service (800) 424-7833

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components (CAS#)	Wt. %	ACGIH TLV:	OSHA PEL:	Ceiling Limit Value:
PTFE 9002-84-0	100%	None	None	None

Notes:

See additional exposure information in Section 8.

3. HAZARDS IDENTIFICATION

NFPA Rating: Health: 2, Flammability: 1, Reactivity: 0

HMIS Classification: Health: 2, Flammability: 1, Reactivity: 0

Emergency Overview: Dust from this product may be harmful if inhaled. High-heat processing may liberate toxic gases. See sections 4, 5 and 10 for more information on thermal decomposition products.

Potential Health Effects:

Skin Contact: Generally does not cause skin irritation.
Eye Contact: May cause irritation to the eyes due to mechanical abrasion of particles.
Ingestion: Ingestion may cause irritation to the gastrointestinal tract.
Inhalation: High concentrations of airborne dust may cause irritation to the respiratory tract.
Medical Conditions Aggravated by Exposure: None known

4. FIRST AID MEASURES

Inhalation: Move to fresh air and monitor for symptoms. If cough or irritation develops, give a glass of water. Never give anything by mouth to an unconscious person. If symptoms persist seek medical attention.
Skin Contact: Wash material from the skin with plenty of soap and water.
Ingestion: If person is conscious, rinse mouth with water. Never give anything by mouth to an unconscious person.
Eye Contact: Flush eyes with plenty of water while holding eyelids open.
Notes to Physician: High heat processing of this product liberates thermal decomposition gases,

FLUON TL-102

Product ID#:610102200

Effective Date:

10/07/2005

which when inhaled can result in polymer fume fever. This condition is characterized by influenza type symptoms (fever, cough and malaise), which usually occurs within a few hours and resolves within 48 hours. Following severe exposure the patient should be kept under medical surveillance for at least 48 hours since delayed pulmonary edema may develop.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Use media suitable for surrounding fire. Product does not support combustion or flame
Unusual Fire and Explosion Hazards:	None known
Hazardous Decomposition Products:	See Section 10.
Flash Point (°F):	
Flash Point (°C):	Not applicable
Autoignition Temperature (°F):	Not applicable
Flammable Limits in Air	
Lower (%):	Not applicable
Upper (%):	Not applicable
Special Protective Equipment for Firefighters:	Wear a self-contained breathing apparatus (SCBA) to prevent inhalation of toxic thermal decomposition products.
Specific Methods:	Evacuate area and restrict access to area. Use fire fighting methods suitable for surrounding fire. This product does not readily burn. Keep containers cool with water spray if possible.

6. ACCIDENTAL RELEASE MEASURES

Containment Techniques:	Restrict area where spill occurred. Tarp spilled material if outdoors to prevent wind dispersion until clean up can occur.
Environmental Protection:	No special environmental precautions required.
Methods for Cleaning Up:	Refer to Section 8 for exposure controls. Restrict area. Ensure adequate ventilation. Gently sweep or vacuum spilled material and collect for disposal. Mop or wipe residual from surface using water.

7. HANDLING AND STORAGE

Safe Handling Precautions:	Avoid creating dust and heating above 260 °C (PTFE). If these conditions cannot be avoided, use adequate ventilation to capture dust or decomposition products at the source.
Safe Storage Conditions:	Keep containers tightly closed in a cool, well-ventilated place.
Incompatible Products:	None known

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Provide local exhaust ventilation in your process to capture dust or thermal decomposition gases at their source. Refer to the ACGIH Guide to Industrial Ventilation for design assistance.
Personal Protective Equipment Respiratory Protection:	Wear a NIOSH approved air-purifying respirator when needed to maintain dust exposures below the limits found in Section-2. Series-100 or HEPA filters are recommended. NOTE: A supplied-air respirator or self-contained breathing

Hand Protection: apparatus (SCBA) must be used to protect against thermal decomposition products.
Skin and Body Protection: Rubber gloves
 Wear full-length work clothes to prevent skin contact. Launder on a routine basis. Do not bring work clothes home.
Eye Protection: Wear tightly-fitting safety goggles in a dusty environment.
Hygiene Measures: Avoid contact with skin, eyes and personal clothing. Do not contaminate tobacco products. Wash hands thoroughly before eating.
Exposure Guidelines PTFE and FEP powders fall in the category of "Particulates Not Otherwise Specified" with the following generic exposure limits: OSHA PEL: 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid
Appearance: Powder
Color: White
Odor: None
Ph: Neutral to slightly acidic in nature.
Boiling Point/Range: Not applicable
Melting Point/Range: 320 - 345 C
Specific Gravity: 2.14-2.18
Bulk Density: 300-600 grams/liter
Solubility in Water: Insoluble
Solubility in Other Solvents: Insoluble in all common solvents.

10. STABILITY AND REACTIVITY

Stability: Decomposes in open air or in nitrogen above 400 °C
Polymerization: None under normal processing.
Hazardous Decomposition Products: Thermal decomposition of this product (at temperatures above 300C.) will generate hydrogen fluoride and hydrogen chloride, which are corrosive.
Materials to Avoid: Reacts with molten alkali metals and finely divided magnesium and aluminum at temperatures above 425 Deg. C
Conditions to Avoid: Avoid temperatures above 380 °C. Continuous use temperature should not exceed 260 °C. (PTFE)

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY AND SKIN DESIGNATION

Components (CAS#)	Wt. %	NIOSH - Selected LD50s & LC50s	ACGIH 2000 - Skin Absorption Designation
PTFE 9002-84-0	100%	= 45 mg/m ³ Inhalation LC50 Rat 30 min	No Data Available

CHRONIC TOXICITY

Carcinogenic effects: No data is available on the product itself, however the monomer used to produce FEP, Tetrafluoroethylene, is known to the state of California to cause cancer.
Mutagenic effects: No data is available on the product itself.
Reproductive toxicity: No data is available on the product itself.

Carcinogenic Status

FLUON TL-102

Product ID#:610102200

Effective Date:

10/07/2005

Components (CAS#)	Wt. %	IARC Carcinogens	ACGIH 1999 - Carcinogens	OSHA - Select Carcinogens	NTP Eighth Report - Known Carcinogens
PTFE 9002-84-0	100%	Not Listed	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Mobility: The product is insoluble and sinks in water.

PTFE 100% 9002-84-0

Clean Water Act - Bioaccumulative Chemical

No data available

Ecotoxicity - Microtox Data

No data available

Ecotoxicity - Aquatic Toxicity Data

No data available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of in accordance with federal, state and local regulations. This product is not a hazardous waste under RCRA, 40 CFR 261 in its original form. If this product is mixed with other materials and/or physically changed, it should be evaluated to assure that the resulting mixture/material does not meet the criteria for listing hazardous waste as specified in 40 CFR 261.11.

Contaminated packaging:

Empty containers should not be used for materials other than the original product. A qualified drum management or solid waste disposal contractor should be used to assure proper handling of empty containers.

14. TRANSPORT INFORMATION

Not regulated by the DOT as hazardous material as determined in 49 CFR 172.

15. REGULATORY INFORMATION

CLEAN AIR ACT REGULATIONS

Components (CAS#)	Wt. %	California - Proposition 65
PTFE 9002-84-0	100%	Not Listed

CALIFORNIA - PROP 65 REGULATIONS

FLUON TL-102

Product ID#:610102200
Page 4 of 6

Effective Date: 10/07/2005

Components (CAS#)	Wt. %	Accidental Release Prevention - Flammable Substances	Accidental Release Prevention - Toxic Substances	1990 Hazardous Air Pollutants	Section 302 - EHS & TPQs	Section 313 - Emissions Reporting	Section 302 - Hazardous Substances	Canadian DSL and NDSL Listing	DSL (Canada):
PTFE 9002-84-0	100%	Not Listed.	Not Listed.	Not Listed.	Not Listed.	Not Listed.	Not Listed.	Not Listed.	on DSL

JENCS (Japan): Listed.
 EINECS (Europe): Listed.
 ELINCS (Europe): Listed.

CHEMICAL INVENTORIES STATUS

Components (CAS#)	Wt. %	New Jersey Know List:	Right-to-Know List:	Pennsylvania Right to Know List:	PICCS (Philippines):
PTFE 9002-84-0	100%	Not Listed.	Not Listed.	Not Listed.	

Sara Classification: Not Classified.

TSCA & CERCLA/SARA REGULATIONS

STATES RIGHT-TO-KNOW LISTS

TSCA (United States): Components (CAS#)	Wt. %	Listed.	TSCA - Sect. 5(a)(2) - Chemicals with SNUR
PTFE 9002-84-0	100%	Not Listed.	

16. OTHER INFORMATION

This data sheet contains changes from the previous version in section(s):
 None

Additional advice:
 No additional informations.

Prepared by: AGCCA Research & Development

Disclaimer:
 The information provided herein is related only to the specific product designated and may not be applicable where such product is used in combination with any other materials or in any process. NO REPRESENTATIONS OR WARRANTIES,

EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE, ARE MADE HEREUNDER. The user of this product has the sole responsibility to determine the suitability of the product for any use and manner of use intended. This document may be revised after its issuance, and the user should refer to the most current version.

End of safety data sheet