

MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Revision Date 11/19/2014 Page 1 of 7 Print Date 11/21/2014

1. HEXPOL Compounding 14330 Kinsman Road, Bui		UCT AND COMPANY IDENTIFICATION H 44021
Telephone Emergency telephone	:	Product Stewardship (440) 834-4644 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ACCU-WAY 4487 - 2.641 KG
Product code	:	AD3000384560
Chemical Name	:	{** [E] POLY1 - Z0000000010061 **}
CAS-No.	:	{** [E] POLY1 - Z0000000010061 **}
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Stearic acid	57-11-4	5 - 10
Zinc oxide	1314-13-2	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	 Irritating to respiratory system. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

4. FIRST AID MEASURES



MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Page 2 of 7 Revision Date 11/19/2014 Print Date 11/21/2014 : Move to fresh air. When symptoms persist or in all cases of doubt Inhalation seek medical advice. Ingestion Do not induce vomiting without medical advice. Seek medical • attention if necessary. Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. **5. FIRE-FIGHTING MEASURES** Flash point : not applicable Flammable Limits Upper explosion limit not applicable : Lower explosion limit not applicable : Autoignition temperature No data available : Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon : dioxide ... Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : pressure mode should be worn to prevent inhalation of airborne Procedures contaminants. Unusual Fire/Explosion : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazards (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES : Avoid breathing dust. Avoid dust formation. Ensure adequate Personal precautions ventilation. Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Do not create a powder • cloud by using a brush or compressed air. Shovel into suitable container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Provide for appropriate exhaust ventilation and dust collection at : machinery. Avoid formation of dust and aerosols.

Storage

: Store in a cool dry place. Keep away from open flames, hot surfaces and sources of ignition.



MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Revision Date 11/19/2014 Page 3 of 7 Print Date 11/21/2014

Respiratory protection	:	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Employees using respirators must be properly trained. Employers must follow applicable regulations such as OSHA 29 CFR 1910.134.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves. Refer to equipment supplier to ensure protection.
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.
Engineering measures	:	Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.



MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Revision Date 11/19/2014 Page 4 of 7 Print Date 11/21/2014

Components	Value	Exposure time	Exposure type	List:
Zinc oxide	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Short Term Exposure Limit (STEL):	Respirable fraction.	ACGIH
	5 mg/m3	Recommended exposure limit (REL):	Fume.	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Dust.	NIOSH
	15 mg/m3	Ceiling Limit Value and Time Period (if specified):	Dust.	NIOSH
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	NIOSH
	5 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Fume.	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Fume.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility Solid
powder, Crumb, pellets
NO PIGMENT
Very faint
not applicable
Not applicable
negligible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not determined
Not applicable
not applicable
not applicable

. not applicat

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.

Conditions to avoid

: Heat, flames and sparks.



MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Revision Date 11/19/2014 Page 5 of 7 Print Date 11/21/2014

Incompatible Materials	:	Strong acids and oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57-11-4	Stearic acid	Irritant	Eyes, Skin.
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57-11-4	Stearic acid			
		Dermal LD50	> 5 gm/kg	rabbit
1314-13-2	Zinc oxide	LC50	2500 mg/m3	mouse
		LC50	-	mouse
		Oral	7,950	mousemouse
		LD50Oral	mg/kg7,950	
		LD50	mg/kg	

12. ECOLOGICAL INFORMATION

Persistence and degradability	: No data available	
Environmental Toxicity	: No data available	
Bioaccumulation Potential	: No data available	

Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

Product	:	Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Revision Date 11/19/2014 Page 6 of 7 Print Date 11/21/2014

]	4. TRANSPOF	RT INFORMAT	ION		
U.S. DOT Classification	:	Refer to specif	ic regulation.			
ICAO/IATA (air)	:	Refer to specif	ic regulation.			
IMO / IMDG (maritime)	:	Refer to specif	ic regulation.			
	15	5. REGULATO	RY INFORMA	ΓΙΟΝ		
US Regulations:						
OSHA Status	:	Classified as h	azardous based o	on componen	ts.	
TSCA Status	:	All componen TSCA Invento	nts of this productory.	t are listed or	n or exen	npt from the
US. EPA CERCLA Hazardo	us Sub	stances (40 CFF	R 302)			
not applicable						
California Propositio 65		Not applicable				
SARA Title III Section 302 I	Extrem	ely Hazardous S	Substance			
Unless specific chemicals are	e ident	ified under this s	section, this produ	uct is Not Ap	plicable	under this regul
SARA Title III Section 313	Foxic (Chemicals:				
Unless specific chemicals are	e ident	ified under this s			-	
Chemical Name ZINC COMPOUNDS			1314	S-No.	30.00	percent
			1514	-1,5=2	50.00	- 00.00
Canadian Regulations:						
National Pollutant Re	lease I	nventory (NPRI				Ţ
			CAS-No.	Weigh	t	NPRI ID#
Chemical Name			0110110.	percen		



MATERIAL SAFETY DATA SHEET ACCU-WAY 4487 - 2.641 KG

Version Number 1.0 Revision Date 11/19/2014 Page 7 of 7 Print Date 11/21/2014

WHMIS Classification	:	Not controlled.	
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Not determined	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
		16. OTHER INFORMATION	1
			1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.