

# EXCEL POLYMERS LLC

## MATERIAL SAFETY DATA SHEET



### **POLYBOUND® 305 TMTM-80**

Version Number 1.6  
Revision Date 03/06/2006

Page 1 of 7  
Print Date 2/5/2010

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**EXCEL POLYMERS LLC**  
14330 Kinsman Road, Burton, OH 44021

Telephone : Product Stewardship (440) 834-4644  
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : POLYBOUND® 305 TMTM -80  
Product code : AD0000045360  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components   | CAS-No.     | Weight % |
|--|-------------|----------|
| Tetramethylthiuram monosulfide                       | 97-74-5     | 60 - 100 |
| Silica, amorphous, precipitated and gel              | 112926-00-8 | 1 - 5    |
| Petroleum distillates, hydrotreated light naphthenic | 64742-53-6  | 5 - 10   |
| Petroleum distillates, hydrotreated heavy naphthenic | 64742-52-5  | 10 - 30  |

#### 3. HAZARDS IDENTIFICATION

##### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

##### Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.  
Ingestion : May be harmful if swallowed.  
Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

# EXCEL POLYMERS LLC

## MATERIAL SAFETY DATA SHEET



### **POLYBOUND® 305 TMTM-80**

Version Number 1.6  
Revision Date 03/06/2006

Page 2 of 7  
Print Date 2/5/2010

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions  
Aggravated by Exposure:** : None known.

#### **4. FIRST AID MEASURES**

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

**Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

#### **5. FIRE-FIGHTING MEASURES**

**Flash point** : Not applicable

**Flammable Limits**  
Upper explosion limit : Not applicable  
Lower explosion limit : Not applicable  
Autoignition temperature : Not relevant  
Suitable extinguishing media : water spray, dry powder, foam, carbon dioxide (CO<sub>2</sub>).

**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

**Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

# EXCEL POLYMERS LLC

## MATERIAL SAFETY DATA SHEET



### **POLYBOUND® 305 TMTM-80**

Version Number 1.6  
Revision Date 03/06/2006

Page 3 of 7  
Print Date 2/5/2010

#### **7. HANDLING AND STORAGE**

- |          |   |   |
|----------|---|---|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |
| Storage  | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.       |

#### **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- |                                |   |   |
|--------------------------------|---|---|
| Respiratory protection         | : | No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material. |
| Eye/Face Protection            | : | Safety glasses with side-shields.   |
| Hand protection                | : | Protective gloves.  |
| Skin and body protection       | : | Long sleeved clothing.  |
| Additional Protective Measures | : | Safety shoes.   |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.  |
| Engineering measures           | : | Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.               |

Exposure limit(s)

**EXCEL POLYMERS LLC****MATERIAL SAFETY DATA SHEET****POLYBOUND® 305 TMTM-80**Version Number 1.6  
Revision Date 03/06/2006Page 4 of 7  
Print Date 2/5/2010

| Components   | Value                  | Exposure time                     | Exposure type        | List:   |
|--|------------------------|-----------------------------------|----------------------|---------|
| Petroleum distillates, hydrotreated heavy naphthenic | 500 ppm<br>2,000 mg/m3 | PEL:                              | Vapor.               | OSHA Z1 |
| Petroleum distillates, hydrotreated light naphthenic | 500 ppm<br>2,000 mg/m3 | PEL:                              | Vapor.               | OSHA Z1 |
|  | 5 mg/m3                | Time Weighted Average (TWA):      | Mist.                | ACGIH   |
|  | 10 mg/m3               | Short Term Exposure Limit (STEL): | Mist.                | ACGIH   |
| Silica, amorphous, precipitated and gel              | 10 mg/m3               | Time Weighted Average (TWA):      | Dust.                | ACGIH   |
|  | 5 mg/m3                | PEL:                              | Respirable fraction. | OSHA Z1 |
|  | 15 mg/m3               | PEL:                              | Total dust.          | OSHA Z1 |
|  | 0.8 mg/m3              | Time Weighted Average (TWA):      |                      | Z3      |
|  | 10 mg/m3               | Time Weighted Average (TWA):      |                      | MX OEL  |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                              |                   |                   |
|---------------------|------------------------------|-------------------|-------------------|
| Form                | : Solid                      | Evaporation rate  | : Not applicable  |
| Appearance          | : Crumb                      | Specific Gravity: | : Not determined  |
| Color               | : NO PIGMENT                 | Bulk density      | : Not established |
| Odor                | : Characteristic rubber odor | Vapor pressure    | : Not applicable  |
| Melting point/range | : Not determined             | Vapour density    | : Not applicable  |
| Boiling Point:      | : Not applicable             | pH                | : Not applicable  |
| Water solubility    | : Insoluble                  |                   |                   |

**10. STABILITY AND REACTIVITY**

|                                  |  |
|----------------------------------|--|
| Stability                        | : Stable.  |
| Hazardous Polymerization         | : Will not occur.  |
| Conditions to avoid              | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.   |
| Incompatible Materials           | : Incompatible with strong acids and oxidizing agents.   |
| Hazardous decomposition products | : Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), other hazardous materials, and smoke are all possible. |

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**EXCEL POLYMERS LLC****MATERIAL SAFETY DATA SHEET****POLYBOUND® 305 TMTM-80**

Version Number 1.6  
 Revision Date 03/06/2006

Page 5 of 7  
 Print Date 2/5/2010

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.     | Chemical Name  | Effect   | Target Organ                        |
|-------------|--|----------|-------------------------------------|
| 97-74-5     | Tetramethylthiuram monosulfide                       | toxic    | Refer to LC50 / LD50 Data on MSDS.. |
| 112926-00-8 | Silica, amorphous, precipitated and gel              | Irritant | Respiratory system, Eyes.           |
| 64742-53-6  | Petroleum distillates, hydrotreated light naphthenic | Irritant | Eyes, Skin.                         |
| 64742-52-5  | Petroleum distillates, hydrotreated heavy naphthenic | Irritant | Eyes, Skin.                         |

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name                  | Route     | Value     | Species |
|---------|--------------------------------|-----------|-----------|---------|
| 97-74-5 | Tetramethylthiuram monosulfide | Oral LD50 | 450 mg/kg | rat     |

## Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.    | Chemical Name  | OSHA | IARC | NTP |
|------------|--|------|------|-----|
| 64742-53-6 | Petroleum distillates, hydrotreated light naphthenic | no   | 1    | no  |

## IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

## NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.

**EXCEL POLYMERS LLC**

**MATERIAL SAFETY DATA SHEET**



**POLYBOUND® 305 TMTM-80**

Version Number 1.6  
Revision Date 03/06/2006

Page 6 of 7  
Print Date 2/5/2010

Additional advice : Not applicable

**13. DISPOSAL CONSIDERATIONS**

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : Not applicable

SARA Title III Section 302 Extremely Hazardous Substance  
Not applicable

SARA Title III Section 313 Toxic Chemicals:

# EXCEL POLYMERS LLC

## MATERIAL SAFETY DATA SHEET



### **POLYBOUND® 305 TMTM-80**

Version Number 1.6  
Revision Date 03/06/2006

Page 7 of 7  
Print Date 2/5/2010

Not applicable  
Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D1B

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.