MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW

Version Number 1.2 Revision Date 11/18/2004 EXCEL

Page 1 of 7 Print Date 8/31/2007

1.	PRODUCT AND O	COMPANY IDENTIF	ICATION	
EXCEL POLYMERS LLO	-			
14330 Kinsman Road, Bur				
Telephone	: Product St	ewardship (440) 834-4	644	
Emergency telephone			24hrs for spill, leak, fire, exposure	
number	or acciden		· · · · · · · · · · · · · · · · · · ·	
Product name	: STAN-TO	NE MB-9115 YELLOV	W	
Product code	: AD000010	0460		
Chemical Name	: Mixture			
CAS-No.	: Mixture			
Product Use	: Industrial A	Applications		
2. COMPOS	ITION/INFORMA	TION ON REGULAT	TED INGREDIENTS	
Componen	ts	CAS-No.	Weight %	
Molybdate orange (Lead ch		12656-85-8	60 - 100	
Worlybuite brunge (Deud er	romate pignient)	12000 00 0	00 100	
	3. HAZARI	DS IDENTIFICATIO	N	
			an a	
	EMERG	ENCY OVERVIEW		
user (fabricator) must t etc.) to protect employ		recautions (mechanical	ventilation, respiratory protection,	
ENTIAL HEALTH EFFE	on an		narmanan aran an a	
Routes of Exposure:	: Inhalation,	Ingestion, Skin contact	t	
Acute exposure				
Inhalation	· Particulates	like other inert materi	als can be mechanically irritating	
Ingestion		Particulates, like other inert materials can be mechanically irritating.May be harmful if swallowed.		
			als can be mechanically irritating.	
Eyes				
Skin	: Experience	snows no unusual dern	natitis hazard from routine handling	
Chronic exposure	: Refer to Sec	ction 11 for Toxicologi	cal Information.	
Medical Conditions	: None know	'n.		
Aggravated by Exposure:				
		HARWIG	CK STANDARD	

60 S. Seiberling Street • Akron, Ohio 44305

10000

MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW

Version Number 1.2 Revision Date 11/18/2004



Page 2 of 7 Print Date 8/31/2007

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable water spray, dry powder, foam, carbon dioxide (CO2)none.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW



Version Number 1.2 Revision Date 11/18/2004

Page 3 of 7 Print Date 8/31/2007

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	
8. EXPOS	SUF	RE CONTROLS / PERSONAL PROTECTION	t
Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.	
Eye/Face Protection	:	Safety glasses with side-shields.	
Hand protection	:	Protective gloves.	
Skin and body protection	:	Long sleeved clothing.	
Additional Protective Measures	:	Safety shoes.	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Molybdate orange (Lead chromate pigment)	0.05 mg/m3	Time Weighted Average (TWA):		OSHA
	0.03 mg/m3	OSHA Action level:		OSHA
	0.1 mg/m3	Ceiling Limit Value:		OSHA Z2
	0.01 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	ACGIH
	1 mg/m3	PEL:	as Cr	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range
- : Solid : Pellets, Slabs, sheets : YELLOW Bulk density : Not established : Characteristic rubber odor Vapor pressure : Not applicable : Not determined
 - Vapour density
- Evaporation rate: Not applicableSpecific Gravity:: Not determined : Not established : Not applicable

MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW

Version Number 1.2 Revision Date 11/18/2004 POLYMERS

Page 4 of 7

Print Date 8/31/2007 **Boiling Point:** : Not applicable pH : Not applicable Water solubility : Insoluble **10. STABILITY AND REACTIVITY** Stability : Stable. Hazardous Polymerization Will not occur. : Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible with strong acids and oxidizing agents. Incompatible Materials : Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12656-85-8	Molybdate orange (Lead chromate pigment)	Irritant	Eyes, Skin.
		Systemic effects	central nervous system (CNS), reproductive system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical Name OSHA	IARC	NTP
----------------------------	------	-----

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW

Version Number 1.2 Revision Date 11/18/2004 EXCEL

Page 5 of 7 Print Date 8/31/2007

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW

Version Number 1.2 Revision Date 11/18/2004



Page 6 of 7 Print Date 8/31/2007

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM VI COMPOUNDSLEAD COMPOUNDS, INORGANICLEAD COMPOUNDS	12656-85-8	60.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Molybdate orange (Lead chromate pigment)	12656-85-8	60.00	235
Molybdate orange (Lead chromate pigment)	12656-85-8	60.00	236

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
12656-85-8	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

:	Listed
:	Listed
	:

MATERIAL SAFETY DATA SHEET

STAN-TONE MB-9115 YELLOW

Version Number 1.2 Revision Date 11/18/2004



Page 7 of 7 Print Date 8/31/2007

Philippines PICCS :

16. OTHER INFORMATION

Listed

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.