MATERIAL SAFETY DATA SHEET

STAN-TONE 61MB01 ALUMINUM

Version Number 1.5 Revision Date 08/10/2009 Page 1 of 6 Print Date 2/13/2010

POLYMERS

1. PRODUCT AND COMPANY IDENTIFICATION

EXCEL POLYMERS LLC 14330 Kinsman Road, Burton, OH 44021

Telephone Emergency telephone	:	Product Stewardship (440) 834-4644 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE 61MB01 ALUMINUM
Product code	:	AD0000111760
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Aluminum	7429-90-5	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

MATERIAL SAFETY DATA SHEET

STAN-TONE 61MB01 ALUMINUM

Version Number 1.5 Revision Date 08/10/2009 Page 2 of 6 Print Date 2/13/2010

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes: Rinse immediately with plenty of water, also under the eye least 15 minutes. If eye irritation persists, seek medical atter	
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 not applicable not applicable not applicable water spray, Dry powder, Foam, Carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

STAN-TONE 61MB01 ALUMINUM



Version Number 1.5 Revision Date 08/10/2009 Page 3 of 6 Print Date 2/13/2010

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOS	SUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Pyrophoric powder. as	ACGIH
		(TWA):	Al	
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	5 mg/m3	Time Weighted Average	Pyrophoric powder.	MX OEL
		(TWA):		
	10 mg/m3	Time Weighted Average	Dust.	MX OEL
		(TWA):		

9. PHYSICAL AND CHEM ICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Solid
pellets, Slabs, sheets
NO PIGMENT
Characteristic rubber odor
Not determined
not applicable

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

MATERIAL SAFETY DATA SHEET

STAN-TONE 61MB01 ALUMINUM

Version Number 1.5 Revision Date 08/10/2009 Page 4 of 6 Print Date 2/13/2010

	:	Insoluble			
		10. STABILITY	AND REACTIVITY		
Stability		: Stable.			
Hazardous Polymeri	zation	: Will not occur.			
Conditions to avoid		: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.			
Incompatible Materi	als	: Incompatible	with strong acids and o	oxidizing agents.	
Hazardous decompo products	sition			oxide (CO), oxides of nitrogen nd smoke are all possible.	
	1	1. TOXICOLOG	ICAL INFORMATI	ON	
CAS-No. 7429-90-5	Ch Aluminu	emical Name	Effect Irritant	Target Organ Skin, Respiratory system.	
				ě ě	
			Systemic effects	Eyes, Skin, Respiratory	
				system.	
		12. ECOLOGIC	CAL INFORMATION		
Persistence and degr	adability	12. ECOLOGIC : Not readily bi			
Persistence and degr Environmental Toxi	-	: Not readily bi	odegradable. e not readily available a		
-	city	 Not readily bi Chemicals are polymer matri 	odegradable. e not readily available a x. e not readily available a	J	
Environmental Toxi	city	 Not readily bi Chemicals are polymer matri Chemicals are 	odegradable. e not readily available a x. e not readily available a x.	Nas they are bound within the	
Environmental Toxi Bioaccumulation Po	city	 Not readily bi Chemicals are polymer matri Chemicals are polymer matri not applicable 	odegradable. e not readily available a x. e not readily available a x.	as they are bound within the as they are bound within the	

Contaminated packaging : Recycling is preferred when possible. The generator of waste



MATERIAL SAFETY DATA SHEET

STAN-TONE 61MB01 ALUMINUM



sion Number 1.5 vision Date 08/10/2009			Page 5 of 6 Print Date 2/13/2010
	material has the responsi transportation and dispos state/provincial and local	al in accordance w	
	14. TRANSPORT INFOR	RMATION	
U.S. DOT Classification	: Refer to specific regulation	on.	
ICAO/IATA (air)	: Refer to specific regulation	on.	
IMO / IMDG (maritime)	: Refer to specific regulation	on.	
	15. REGULATORY INFO	RMATION	
US Regulations:			
OSHA Status	: Classified as hazardous b	based on componer	nts.
TSCA Status	: All components of this p TSCA Inventory.	product are listed o	n or exempt from the
US. EPA CERCLA Hazardous	Substances (40 CFR 302)		
not applicable			
California Proposition 65	: WARNING! This produ California to cause birth		tical known to the State of productive harm.
SARA Title III Section 302 Extr	remely Hazardous Substance		
Unless specific chemicals are id	lentified under this section, thi	s product is Not A	pplicable under this regulatior
SARA Title III Section 313 Tox Unless specific chemicals are id		s product is Not A	pplicable under this regulation
Chemical Name ALUMINUM (FUME OR DU	TST)	CAS-No. 7429-90-5	Weight percent 30.00 - 60.00
ALOWINOW (FOME OR DO	551)	7429-90-5	30.00 - 00.00
Canadian Regulations:			
National Pollutant Releas	se Inventory (NPRI)		
	• • •		

MATERIAL SAFETY DATA SHEET

STAN-TONE 61MB01 ALUMINUM



Version Number 1.5 Revision Date 08/10/2009 Page 6 of 6 Print Date 2/13/2010

Chemical Name			CAS-No.	Weight percent	NPRI ID#
Aluminum			7429-90-5	30.00 - 60.00	
WHMIS Classification WHMIS Ingredient Dis		D2B re List			
7429-90-5 DSL ational Inventories:	:		ts of this product t (DSL) or are exe	are on the Canadian empt.	Domestic
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determine	d		
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.