MATERIAL SAFETY DATA SHEET



STAN-TONE CMS 205 YELLOW SLAB

Version Number 1.3 Revision Date 11/16/2004

Page 1 of 6 Print Date *8/17/2006*

1. PRODUCT AND COMPANY IDENTIFICATION

EXCEL POLYMERS LLC

14330 Kinsman Road, Burton, OH 44021

Telephone : Product Stewardship (440) 834-4644

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : STAN-TONE CMS 205 YELLOW SLAB

Product code : AD0000076660

Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	1 - 5
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	1 - 5
Stearic acid	57-11-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Particulates, like other inert materials can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

MARKETED BY

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. Seiberling Street • Akron, Ohio 44305

MATERIAL SAFETY DATA SHEET



STAN-TONE CMS 205 YELLOW SLAB

Version Number 1.3 Revision Date 11/16/2004

Page 2 of 6 Print Date *8/17/2006*

Chronic exposure

: Refer to Section 11 for Toxicological Information.

Medical Conditions

Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit
Lower explosion limit

Autoignition temperature

Suitable extinguishing media

: Not applicable

Not applicable Not applicable

: water spray, dry powder, foam, carbon dioxide (CO2)none.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

Unusual Fire/Explosion

Hazards

contaminants.
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section

13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET



STAN-TONE CMS 205 YELLOW SLAB

Version Number 1.3 Revision Date 11/16/2004

Page 3 of 6 Print Date *8/17/2006*

Handling

: Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage

: Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

: No personal respiratory protective equipment normally required when

handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this

material

Eye/Face Protection

: Safety glasses with side-shields.

Hand protection

: Protective gloves.

Skin and body protection

: Long sleeved clothing.

Additional Protective

Safety shoes.

Measures

General Hygiene

Considerations

: Handle in accordance with good industrial hygiene and safety

practice. Wash hands before breaks and at the end of workday.

Engineering measures

Heat only in areas with appropriate exhaust ventilation. Adequate

ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Petroleum distillates, hydrotreated heavy naphthenic	500 ppm 2,000 mg/m3	PEL:	Vapor.	OSHA Z1
Petroleum distillates, hydrotreated light naphthenic	500 ppm 2,000 mg/m3	PEL:	Vapor.	OSHA Z1
Stearic acid	10 mg/m3	Time Weighted Average (TWA):	Total dust. as stearates	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid

Evaporation rate

: Not applicable

Appearance

: Pellets, Slabs, sheets

Specific Gravity:

Not determined

MATERIAL SAFETY DATA SHEET



STAN-TONE CMS 205 YELLOW SLAB

Version Number 1.3 Revision Date 11/16/2004

Page 4 of 6 Print Date 8/17/2006

Color Odor Melting point/range : YELLOW : Characteristic rubber odor Vapor pressure : Not determined

Bulk density Vapour density

: Not established Not applicable : Not applicable

Boiling Point: Water solubility : Not applicable : Insoluble

рН

: Not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.

Conditions to avoid

Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials

: Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
64742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	Irritant	Eyes, Skin.
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	Irritant	Eyes, Skin.
57-11-4	Stearic acid	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57-11-4	Stearic acid			1
		Dermal LD50	> 5 gm/kg	rabbit

12. ECOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET



STAN-TONE CMS 205 YELLOW SLAB

Version Number 1.3 Revision Date 11/16/2004 Page 5 of 6 Print Date 8/17/2006

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice : Not applicable

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : WARNING! This product contains a chemical known to the State of

California to cause cancer.

MATERIAL SAFETY DATA SHEET



STAN-TONE CMS 205 YELLOW SLAB

Version Number 1.3 Revision Date 11/16/2004 Page 6 of 6 Print Date *8/17/2006*

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification

: D2B

WHMIS Ingredient Disclosure List

CAS-No. 57-11-4

DSL

All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS

Not determined

China IECS

: Not determined

Europe EINECS

: Not determined

Japan ENCS

Not determined

Korea KECI

Not determined

Philippines PICCS

Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.