

MATERIAL SAFETY DATA SHEET MMC 55-1056 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012

Page 1 of ∮ Print Date 3/11/2014

1. PRODUCT AND COMPANY IDENTIFICATION				
HEXPOL Compounding 14330 Kinsman Road, Burton, OH 44021				
Telephone Emergency telephone	:	Product Stewardship (440) 834-4644 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	MMC 55-1056 RED DRY PWD-100		
Product code	:	AD3000351560		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Barium sulfate	7727-43-7	5 - 10
Iron oxide	1309-37-1	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Inhalation

Routes	of Exposure:	
--------	--------------	--

Eyes

Skin

Chronic exposure

Inhalation, Ingestion, Skin contact

Acute exposure

- : Particulates, like other inert materials can be mechanically irritating.
- Ingestion : May be harmful if swallowed.
 - : Particulates, like other inert materials can be mechanically irritating.
 - : Experience shows no unusual dermatitis hazard from routine handling.
 - : Refer to Section 11 for Toxicological Information.
- **Medical Conditions** : None known. Aggravated by Exposure:

:



MATERIAL SAFETY DATA SHEET *MMC 55-1056 RED DRY PWD-100*

Version Number 1.1 Revision Date 03/08/2012 Page 2 of 6 Print Date 3/11/2014

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptom persist or in all cases of doubt seek medical advice.	3
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: not applicable	
Flammable Limits		
Upper explosion limit	: not applicable	
Lower explosion limit	: not applicable	
Autoignition temperature	: not applicable	
Suitable extinguishing media	: Water spray, Dry powder, Foam, Carbon dioxide (CO2).	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroger (NOx), other hazardous materials, and smoke are all possible.	1
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Secti 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. He only in areas with appropriate exhaust ventilation.	ıt
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	m



MATERIAL SAFETY DATA SHEET MMC 55-1056 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012 Page 3 of 6 Print Date 3/11/2014

and contamination. Keep in a dry, cool place.		
8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Barium sulfate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES



MATERIAL SAFETY DATA SHEET *MMC 55-1056 RED DRY PWD-100*

Version Number 1.1 Revision Date 03/08/2012 Page 4 of 6 Print Date 3/11/2014

	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50	22,500 mg/kg	rat

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.



MATERIAL SAFETY DATA SHEET MMC 55-1056 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012 Page 5 of 6 Print Date 3/11/2014

Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regula



MATERIAL SAFETY DATA SHEET *MMC 55-1056 RED DRY PWD-100*

Version Number 1.1 Revision Date 03/08/2012 Page 6 of 6 Print Date 3/11/2014

SARA Title III Section 313 Toxic Chemicals:					
Unless specific chemicals are id	Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
Canadian Regulations:					
National Pollutant Release	se Ir	aventory (NPRI)			
not applicable					
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Listed			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.