

## MATERIAL SAFETY DATA SHEET MMC 50-1071 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012 Page 1 of 1 Print Date 3/24/2012

HEXPOL Compounding 14330 Kinsman Road, Burto Telephone	on OH 44021	
Emergency telephone	<ul> <li>Product Stewardship (440) 834-4644</li> <li>CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposur</li> </ul>	
	or accident).	
Product name	: MMC 50-1071 RED DRY PWD-100	
Product code	: AD3000352660	
Chemical Name	: Mixture	
CAS-No.	: Mixture	
Product Use	: Industrial Applications	
2. COMPOSI	TION/INFORMATION ON REGULATED INGREDIENTS	
There are no known hazardow	is components above regulatory thresholds in this product.	
	3. HAZARDS IDENTIFICATION	
STATISTICTICTICTICTICTICTICTICTICTICTICTICTICT	RERETERATION DE LE RECERCIENTE DE LE RE	
	EMERGENCY OVERVIEW	
This mixture has not been	en evaluated as a whole. Information provided on the health effects of this	
	vidual components. All ingredients are bound and potential for hazardous	
exposure as shipped is n	ninimal. However, some vapors may be released upon heating and the end-	
user (fabricator) must ta	ke the necessary precautions (mechanical ventilation, respiratory protection,	
etc.) to protect employee	es from exposure.	
	NARAMANANANANANANANANANANANANANANANANANA	
ENTIAL HEALTH EFFEC	CTS	
Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation	lation : Particulates, like other inert materials can be mechanically irritating.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Particulates, like other inert materials can be mechanically irritating.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling	
	: Refer to Section 11 for Toxicological Information.	
Chronic exposure		
-	· None known	
Chronic exposure Medical Conditions Aggravated by Exposure:	: None known.	



# MATERIAL SAFETY DATA SHEET MMC 50-1071 RED DRY PWD-100

sion Number 1.1 <i>r</i> ision Date 03/08/2012	Page Print Date 3/24
	overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Autoignition temperature	: not applicable
Suitable extinguishing media	: Water spray, Dry powder, Foam, Carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Tiocedures	contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPO	OSURE CONTROLS/PERSONAL PROTECTION



## MATERIAL SAFETY DATA SHEET MMC 50-1071 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012 Page 3 of 3 Print Date 3/24/2012

	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.		
Eye/Face Protection	:	Safety glasses with side	-shields	
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene Considerations	:	Handle in accordance w practice. Wash hands b		
Engineering measures	:	: Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.		
Exposure limit(s)				
9. Form	PHYS : So	SICAL AND CHEMIC	AL PROPERTIES	: Not applicable
Appearance	-	: pellets, Slabs, sheets Specific Gravity : Not determined		: Not determined
Color	: RI		Bulk density	: Not established
Color Odour	: Cł	naracteristic rubber odor	Vapour pressure	: not applicable
Color Odour Melting point/range	: Ch : No	naracteristic rubber odor ot determined	Vapour pressure Vapour density	<ul><li>not applicable</li><li>not applicable</li></ul>
Color Odour	: Cł : No : no	naracteristic rubber odor	Vapour pressure	: not applicable
Color Odour Melting point/range Boiling Point:	: Ch : No : no : Ins	haracteristic rubber odor ot determined t applicable	Vapour pressure Vapour density pH	<ul><li>not applicable</li><li>not applicable</li></ul>
Color Odour Melting point/range Boiling Point:	: Ch : No : no : Ins	haracteristic rubber odor ot determined t applicable soluble	Vapour pressure Vapour density pH	<ul><li>not applicable</li><li>not applicable</li></ul>
Color Odour Melting point/range Boiling Point: Water solubility	: Ch : No : no : Ins	aaracteristic rubber odor ot determined t applicable soluble <b>. STABILITY AND RE</b>	Vapour pressure Vapour density pH	<ul><li>not applicable</li><li>not applicable</li></ul>
Color Odour Melting point/range Boiling Point: Water solubility Stability	: Ch : No : no : Ins	aracteristic rubber odor ot determined t applicable soluble <b>. STABILITY AND RE</b> Stable.	Vapour pressure Vapour density pH EACTIVITY	: not applicable : not applicable : not applicable
Color Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	: Ch : No : no : Ins	aaracteristic rubber odor ot determined t applicable soluble <b>. STABILITY AND RE</b> Stable. Will not occur. Keep away from oxidizi	Vapour pressure Vapour density pH EACTIVITY ng agents and open flaverheat.	: not applicable : not applicable : not applicable ame. To avoid thermal
Color Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization Conditions to avoid	: Ch : No : no : Ins	A aracteristic rubber odor ot determined t applicable soluble <b>. STABILITY AND RE</b> Stable. Will not occur. Keep away from oxidizi decomposition, do not o	Vapour pressure Vapour density pH EACTIVITY ng agents and open fla werheat. g acids and oxidizing carbon monoxide (CC	: not applicable : not applicable : not applicable ame. To avoid thermal agents. ), oxides of nitrogen



## MATERIAL SAFETY DATA SHEET MMC 50-1071 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012 Page 4 of 4 Print Date 3/24/2012

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	
	4/4



## MATERIAL SAFETY DATA SHEET MMC 50-1071 RED DRY PWD-100

Version Number 1.1 Revision Date 03/08/2012 Page 5 of 5 Print Date 3/24/2012

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
BARIUM COMPOUNDS [EXCEPT BASO4]	7585-41-3	60.00 - 100.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.