

MATERIAL SAFETY DATA SHEET MMC 70-1170 YELLOW DRY PWD-100

Version Number 1.0 Revision Date 06/12/2012 Page 1 of 5 Print Date 6/12/2012

39

25

HEXPOL Compounding 14330 Kinsman Road, Burton, OH 44021				
Felephone E mergency telephone	:	Product Stewardship (440) 834-4644 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	MMC 70-1170 YELLOW DRY PWD-100		
Product code	:	AD3000366660		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		
2. COMPOS	ITION/	INFORMATION ON REGULATED INGREDIENTS		
There are no known hazardo	ous com	ponents above regulatory thresholds in this product.		

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact			
Acute exposure				
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:	: None known.			
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from			



MATERIAL SAFETY DATA SHEET MMC 70-1170 YELLOW DRY PWD-100

sion Number 1.0 ision Date 06/12/2012	Page 2 Print Date 6/12/2
	overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Water spray, Dry powder, Foam, Carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSURE CONTROLS/PERSONAL PROTECTION



MATERIAL SAFETY DATA SHEET MMC 70-1170 YELLOW DRY PWD-100

Version Number 1.0 Revision Date 06/12/2012

Page 3 of 5 Print Date 6/12/2012

Respiratory protection	: No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.		
Eye/Face Protection	: Safety glasses with side-shields		
Hand protection	: Protective gloves		
Skin and body protection	: Long sleeved clothing		
Additional Protective Measures	: Safety shoes		
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.		
	us components above regulatory thresholds in this product.		
9	P. PHYSICAL AND CHEMICAL PROPERTIES		
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	PHYSICAL AND CHEMICAL PROPERTIES : Solid Evaporation rate : Not applicable : pellets, Slabs, sheets Specific Gravity : Not determined : YELLOW Bulk density : Not established : Characteristic rubber odor Vapour pressure : not applicable : Not determined Vapour density : not applicable : not applicable pH : not applicable : Insoluble : : Not applicable		
Form Appearance Color Odour Melting point/range Boiling Point:	: SolidEvaporation rate: Not applicable: pellets, Slabs, sheetsSpecific Gravity: Not determined: YELLOWBulk density: Not established: Characteristic rubber odorVapour pressure: not applicable: Not determinedVapour density: not applicable: not applicablepH: not applicable		
Form Appearance Color Odour Melting point/range Boiling Point:	: Solid Evaporation rate : Not applicable : pellets, Slabs, sheets Specific Gravity : Not determined : YELLOW Bulk density : Not established : Characteristic rubber odor Vapour pressure : not applicable : Not determined Vapour density : not applicable : not applicable pH : not applicable : Insoluble		
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	: SolidEvaporation rate: Not applicable: pellets, Slabs, sheetsSpecific Gravity: Not determined: YELLOWBulk density: Not established: Characteristic rubber odorVapour pressure: not applicable: Not determinedVapour density: not applicable: not applicablepH: not applicable: InsolubleInsoluble: not applicable		
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility Stability	: Solid Evaporation rate : Not applicable : pellets, Slabs, sheets Specific Gravity : Not determined : YELLOW Bulk density : Not established : Characteristic rubber odor Vapour pressure : not applicable : Not determined Vapour density : not applicable : not applicable pH : not applicable : Insoluble Insoluble : Not applicable : Stable. : Stable. : Stable.		
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	 Solid Evaporation rate : Not applicable pellets, Slabs, sheets Specific Gravity : Not determined YELLOW Bulk density : Not established Characteristic rubber odor Vapour pressure : not applicable Not determined Vapour density : not applicable not applicable pH : not applicable Insoluble 10. STABILITY AND REACTIVITY Stable. Will not occur. Keep away from oxidizing agents and open flame. To avoid thermal 		



MATERIAL SAFETY DATA SHEET MMC 70-1170 YELLOW DRY PWD-100

Version Number 1.0 Revision Date 06/12/2012 Page 4 of 5 Print Date 6/12/2012

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	



MATERIAL SAFETY DATA SHEET MMC 70-1170 YELLOW DRY PWD-100

Version Number 1.0 Revision Date 06/12/2012 Page 5 of 5 Print Date 6/12/2012

California Proposition 65	:	Not applicable			
SARA Title III Section 302 Extremely Hazardous Substance					
Unless specific chemicals are id	Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
SARA Title III Section 313 Toxic Chemicals:					
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation					
Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
not applicable					
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Listed			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.