

MATERIAL SAFETY DATA SHEET MMC 00-1262 VIOLET EM SLAB-45

Version Number 1.0 Revision Date 02/08/2013 Page 1 of 6 Print Date 2/8/2013

HEXPOL Compounding 14330 Kinsman Road, Bu	rton, OH 44021		
Telephone Emergency telephone			4 hrs for spill, leak, fire, exposure
Product name		-1262 VIOLET EM SLAB	-45
Product code	: AD30003	375860	
Chemical Name CAS-No.	: Mixture : Mixture		
Product Use		Applications	
2. COMPOS	ITION/INFORM	ATION ON REGULATE	CD INGREDIENTS
Componer	nts	CAS-No.	Weight percent
Calcium carbonate		471-34-1	10 - 30
	3. HAZAR	RDS IDENTIFICATION	
product is based on ind exposure as shipped is user (fabricator) must	een evaluated as a dividual component minimal. Howeve take the necessary	ts. All ingredients are bou er, some vapors may be rele precautions (mechanical ve	ed on the health effects of this nd and potential for hazardous eased upon heating and the end- entilation, respiratory protection,
product is based on ind exposure as shipped is	een evaluated as a dividual component minimal. Howeve take the necessary yees from exposure.	whole. Information provid ts. All ingredients are bou er, some vapors may be rele precautions (mechanical ve	nd and potential for hazardous eased upon heating and the end-
product is based on ind exposure as shipped is user (fabricator) must etc.) to protect employ	een evaluated as a dividual component minimal. Howeve take the necessary p rees from exposure.	whole. Information provid ts. All ingredients are bou er, some vapors may be rele precautions (mechanical ve	nd and potential for hazardous eased upon heating and the end-
product is based on ind exposure as shipped is user (fabricator) must etc.) to protect employ ENTIAL HEALTH EFFE	een evaluated as a dividual component minimal. Howeve take the necessary p rees from exposure.	whole. Information provid ts. All ingredients are bou er, some vapors may be rele precautions (mechanical ve	nd and potential for hazardous eased upon heating and the end-
product is based on ind exposure as shipped is user (fabricator) must etc.) to protect employ ENTIAL HEALTH EFFE Routes of Exposure:	een evaluated as a dividual component minimal. Howeve take the necessary p rees from exposure. CCTS : Inhalation : Particulate : May be ha : Particulate	whole. Information provid ts. All ingredients are bou er, some vapors may be rele precautions (mechanical va n, Ingestion, Skin contact es, like other inert materials rmful if swallowed. es, like other inert materials	nd and potential for hazardous eased upon heating and the end-
product is based on ind exposure as shipped is user (fabricator) must etc.) to protect employ ENTIAL HEALTH EFFE Routes of Exposure: Acute exposure Inhalation Ingestion Eyes	een evaluated as a dividual component minimal. Howeve take the necessary p rees from exposure. CCTS : Inhalation : Particulate : May be ha : Particulate : Experience	whole. Information provid ts. All ingredients are bou er, some vapors may be rele precautions (mechanical va n, Ingestion, Skin contact es, like other inert materials rmful if swallowed. es, like other inert materials	nd and potential for hazardous eased upon heating and the end- entilation, respiratory protection, s can be mechanically irritating. s can be mechanically irritating. it is hazard from routine handling
product is based on ind exposure as shipped is user (fabricator) must etc.) to protect employ ENTIAL HEALTH EFFE Routes of Exposure: Acute exposure Inhalation Ingestion Eyes Skin	een evaluated as a dividual component minimal. Howeve take the necessary p rees from exposure. CCTS : Inhalation : Particulate : May be ha : Particulate : Experience	whole. Information provid ts. All ingredients are bou er, some vapors may be rele precautions (mechanical ve n, Ingestion, Skin contact es, like other inert materials rmful if swallowed. es, like other inert materials e shows no unusual dermat ection 11 for Toxicological	nd and potential for hazardous eased upon heating and the end- entilation, respiratory protection, s can be mechanically irritating. s can be mechanically irritating. it is hazard from routine handling



MATERIAL SAFETY DATA SHEET MMC 00-1262 VIOLET EM SLAB-45

sion Date 02/08/2013		Page 2 Print Date 2/8/2
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
		Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	: :	not applicable not applicable not applicable Water spray, Dry powder, Foam, Carbon dioxide (CO2). Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards		(NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.



MATERIAL SAFETY DATA SHEET MMC 00-1262 VIOLET EM SLAB-45

Version Number 1.0 Revision Date 02/08/2013 Page 3 of 6 Print Date 2/8/2013

8. EXPOSURE CONTROLS/PERSONAL PROTECTION		
Respiratory protection	: No personal respiratory protective equipment normally required w handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.	
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	15 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range
- Solid
 pellets, Slabs, sheets
 RED
 Characteristic rubber odor
 Not determined
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable



MATERIAL SAFETY DATA SHEET MMC 00-1262 VIOLET EM SLAB-45

Version Number 1.0 Revision Date 02/08/2013 Page 4 of 6 Print Date 2/8/2013

Boiling Point: Water solubility	: not applicable : Insoluble	pН	: not applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	00	open flame. To avoid thermal
Incompatible Materials	: Incompatible with	strong acids and oxid	dizing agents.
Hazardous decomposition products			le (CO), oxides of nitrogen smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50Oral LD50Oral	6,450 mg/kg6,450 mg/kg6,450	ratratmouse
		LD50	mg/kg	

12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	: not applicable	
	13. DISPOSAL CONSIDERATIONS	



MATERIAL SAFETY DATA SHEET MMC 00-1262 VIOLET EM SLAB-45

ion Number 1.0 ision Date 02/08/2013	Page 5 Print Date 2/8/2
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regula
SARA Title III Section 313	Toxic Chemicals:
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regula



MATERIAL SAFETY DATA SHEET MMC 00-1262 VIOLET EM SLAB-45

Version Number 1.0 Revision Date 02/08/2013 Page 6 of 6 Print Date 2/8/2013

Canadian Regulations:

National Pollutant Release Inventory (NPRI)				
not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Listed		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.