

MATERIAL SAFETY DATA SHEET VVO CAR BEL EX 20 CAKE

Version Number 1.5 Revision Date 11/09/2011 Page 1 of 6 Print Date 6/4/2013

HEXPOL Compounding 14330 Kinsman Road, Bur	rton, Ol	H 44021
Telephone E mergency telephone	:	Product Stewardship (440) 834-4644 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	VVO CAR BEL EX 20 CAKE
Product code	:	AD00000757X1
Chemical Name	:	Soybean oil, sulfurized
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components	CAS-No.	Weight percent
Petroleum distillates, hydrotreated light	64742-53-6	1 - 5
naphthenic		
Petroleum distillates, hydrotreated heavy	64742-52-5	5 - 10
naphthenic		
Calcium carbonate	1317-65-3	10 - 30
Extracts, petroleum, heavy paraffinic	64742-04-7	10 - 30
distillate solvent		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product has not been evaluated as a whole for health effects. Some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

997 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1897 : 1

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 At process temperatures, product emissions may cause irritation. May be harmful if swallowed. At process temperatures, product emissions may cause irritation. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET VVO CAR BEL EX 20 CAKE

Version Number 1.5 Revision Date 11/09/2011 Page 2 of 6 Print Date 6/4/2013

Aggravated by Exposure:	A EIDET AID MEASUDES
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 not applicable not applicable Not relevant Water, Dry powder, Foam, Carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: No special precautions required.



MATERIAL SAFETY DATA SHEET VVO CAR BEL EX 20 CAKE

Version Number 1.5 Revision Date 11/09/2011 Page 3 of 6 Print Date 6/4/2013

8.]	EXPOSUR	E CONTROLS/PERSONAL	PROTECTION	
Respiratory protection	:	No personal respiratory protect	ive equipment normally r	equired.
Eye/Face Protection	:	Safety glasses with side-shields	8	
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene:Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures : Heat only in areas with appropriate exhaust ventilation.				
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1

	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Petroleum distillates, hydrotreated heavy naphthenic	500 ppm 2,000 mg/m3	PEL:		OSHA Z1
Petroleum distillates, hydrotreated light naphthenic	500 ppm 2,000 mg/m3	PEL:		OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Mist.	ACGIH
	10 mg/m3	Short Term Exposure Limit (STEL):	Mist.	ACGIH
Extracts, petroleum, heavy paraffinic distillate solvent	5 mg/m3	Time Weighted Average (TWA):	Mist.	ACGIH
	10 mg/m3	Short Term Exposure Limit (STEL):	Mist.	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid : Crumb, bales Evaporation rate Specific Gravity Not applicableNot determined



MATERIAL SAFETY DATA SHEET **VVO CAR BEL EX 20 CAKE**

Version Number 1.5 Revision Date 11/09/2011

Page 4 of 6 Print Date 6/4/2013

Color Odour Melting point/range Boiling Point: Water solubility	 NO PIGMENT Characteristic rubber odor Not determined not applicable not applicable Insoluble 	
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: None known.	
Incompatible Materials	: Strong acids and oxidizing agents, Alkali metals	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
64742-53-6	Petroleum distillates,	Irritant	Eyes, Skin.
	hydrotreated light		
	naphthenic		
64742-52-5	Petroleum distillates,	Irritant	Eyes, Skin.
	hydrotreated heavy		
	naphthenic		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
64742-53-6	Petroleum distillates,	no	1	no
	hydrotreated light naphthenic			
64742-04-7	Extracts, petroleum, heavy paraffinic distillate solvent	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.



MATERIAL SAFETY DATA SHEET VVO CAR BEL EX 20 CAKE

Version Number 1.5

Page 5 of 6 Print Date 6/4/2013

Revision Date 11/09/2011 2A - The component is probably carcinogenic to humans. 2B - The component is possibly carcinogenic to humans. NTP Carcinogen Classifications: 1 - The component is known to be a human carcinogen. 2 - The component is reasonably anticipated to be a human carcinogen. **12. ECOLOGICAL INFORMATION** Persistence and degradability Not readily biodegradable. : Environmental Toxicity No data available **Bioaccumulation Potential** No data available Additional advice not applicable : **13. DISPOSAL CONSIDERATIONS** Where possible recycling is preferred to disposal or incineration. The Product : generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification Not regulated for transportation. : ICAO/IATA (air) Not regulated for transportation. : IMO / IMDG (maritime) Not regulated for transportation. • **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. : **TSCA Status** All components of this product are listed on or exempt from the : TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable



MATERIAL SAFETY DATA SHEET VVO CAR BEL EX 20 CAKE

Version Number 1.5 Revision Date 11/09/2011

Page 6 of 6 Print Date 6/4/2013

California Proposition : Not applicable 65
SARA Title III Section 302 Extremely Hazardous Substance
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 Toxic Chemicals:
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:
National Pollutant Release Inventory (NPRI)
not applicable
WHMIS Classification : D2A
DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.
National Inventories:
Australia AICS : Not determined
China IECS : Not determined
Europe EINECS : Not determined
Japan ENCS : Not determined
Korea KECI : Not determined
Philippines PICCS : Not determined
16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.