



# Product Literature

ISO 9001:2008 REGISTERED

---

**PLASTICZER SC-B**  
**Triethylene glycol dicaprate/dicaprylate**  
CAS# Proprietary

Plasticizer SC-B, a capric-caprylic diester of triethylene glycol, is generally recognized as an ideal softener and low temperature plasticizer for SBR, NBR, CR (polychloroprene), and NR. In addition, it has the effect of reducing the heat hardening properties of these polymers. As a result, it is used in formulations designed to meet automotive, aeronautical and government specifications, including critical FDA applications required under 21 CFR 177.2600(c)(4)(iv).

### **TYPICAL PROPERTIES**

Appearance	Clear to Yellow Liquid
Color, Gardner	1.5
Specific Gravity @ 15°C	0.967
Refractive Index @ 25°C (77°F)	1.4470
Viscosity, SUS @ 68°F	90
Saponification Value	265
Hydroxyl Value	10
Free Fatty Acid (as Oleic), %	.10
Moisture, %	0.1

8/11/98 – Revised 10/28/13

---

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT OR SPECIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

### **HARWICK STANDARD DISTRIBUTION CORPORATION**

60 S. SEIBERLING ST. • P.O. BOX 9360 • AKRON, OH 44305-0360 • U.S.A.  
PHONE: (330) 798-9300 • FAX: (330) 798-0214  
WWW.HARWICKSTANDARD.COM

## OTHER APPLICATIONS FOR PLASTICIZER SC-B:

- Highly recommended for use as a plasticizer in general vinyl compounding, for any application requiring extreme low temperature flexibility combined with very high plasticizing action.
- Imparts excellent "hand" and drape to vinyl films and is suited for curtain and upholstery materials, tablecloths, fabric coatings and artificial leathers.
- Acts as its own lubricant in vinyl compositions and is used for this purpose in high temperature calendering and embossing operations.
- Works well in plastisols and organosols by providing low viscosity formulations and also used as a viscosity control agent.
- Very effective in all pigmented systems and in dispersion, pastes, and emulsion systems.
- Can be emulsified for the plasticizing of synthetic latices which are used in the paint, protective coatings and other allied industries.
- Enhances the general quality and processability when used in small concentrations, regardless of other plasticizers in the system.
- Used in nitrocellulose lacquers to give increased flexibility at normal and low temperatures.

8/11/98 – Revised 10/28/13

**HARWICK STANDARD DISTRIBUTION CORPORATION**  
60 S. SEIBERLING ST. • P.O. BOX 9360 • AKRON, OH 44305-0360 • U.S.A.  
PHONE: (330) 798-9300 • FAX: (330) 798-0214  
[WWW.HARWICKSTANDARD.COM](http://WWW.HARWICKSTANDARD.COM)